

Michael Abel, et al
Appl. No. 10/562,611
Amdt. dated March 21, 2008
Reply to Office Action of 02/21/2008

REMARKS/ARGUMENTS

In the Office Action, the Examiner indicated that the response previously filed on 5/11/07 and 12/26/07 were not fully responsive because of inadequate identification of the species intended to be elected, and because the previously submitted new drawing figures omitted subject matter relating to the non-elected species (species "a") thereby rendering some of the claims to lack support in the drawing, resulting in a lack of conformance to the specification which still described both species. The Examiner requested submission of a substitute specification because of the numerous amendments to the specification.

In order to clarify these matters, a study of the specification and the claims was conducted with respect to the new drawing figures to determine which subject matter, identified by their respective reference numerals, was no longer present in the drawing. As a result of this study, it was found that three paragraphs of the specification contained references to material that is no longer referenced in the drawing figures. With respect to the first of these paragraphs (which bridges pages 8-9), most of this paragraph is canceled. With respect to the second and the third of these paragraphs (which are found on page 10), these two paragraphs are canceled.


Furthermore, it was found that six of the claims (claims 40-42 and 44-46) contained reference numerals to subject matter no longer referenced by the reference numerals in the new drawing figures. These claims are canceled in the present amendment, it

being understood that the Applicant reserves the right to file these claims in a divisional application with drawing figures showing the claimed subject matter. Two of these claims (claims 44 and 45) were part of the elected set of claims, but are now canceled.

Applicant hereby confirms the election of the species of invention, identified as "species b" and directed to the subject matter of the original figures 8-13 for prosecution with claims 24-39, 43 and 47 being readable on the elected species. The remaining claims 40-42 and 44-46 have subject matter falling within the withdrawn species, identified as "species a" directed to the subject matter of the original figures 1-7 and, as noted above, are canceled.

This application is believed now to in condition for examination on the merits.

Respectfully submitted
Michael Abel, et al


by: 
MARTIN A. FARBER
Attorney for Applicants
Registered Representative
Registration No.: 22,345

CERTIFICATE OF MAILING UNDER 37 CFR SECTION 1.8 (a)

I hereby certify that the accompanying Confirmation of Election and Amendment is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Commissioner for Patents, PO Box 1450, Alexandria, VA 22313-1450, on March 21, 2008.

Dated: March 21, 2007

866 United Nations Plaza
New York, NY 10017
(212) 758-2878


Martin A. Farber



Screwdriver handle with storage chamber for screwdriver bits

FIELD AND BACKGROUND OF THE INVENTION

5 The invention relates to a handle of a screwdriver having a storage chamber for screwdriver bits or the like, the storage chamber being displaceable from a closed position into an open position by axial displacement of two handle parts with respect to one another, one handle part having a
10 core, which is disposed in a cavity in the other handle part, and the two handle parts being held in the closed position of the storage chamber by latching means.

A handle of this type for a screwdriver, or a screwdriver
15 having a handle of this type, is already known from US 5,265,504. The handle has two handle parts. These handle parts can be pulled apart in order to open a storage chamber. Screwdriver inserts, known as bits, are located in the storage chamber and can then be removed. One of the two
20 handle parts, namely the one which carries the blade, has a cavity. In the closed position, the core of the other handle part fits into this cavity. Around the core there are a plurality of compartments for receiving the screwdriver bits. In the closed position, a latching cam engages behind
25 a latching shoulder.

US 6,629,478 B2 has disclosed a screwdriver handle in which a handle part which carries the blade has insertion openings for the insertion of screwdriver bits. This handle part can
30 be pushed into the cavity of another handle part, which forms the end side of the handle, counter to the force of a compression spring. The end side of the handle has an opening for receiving a screwdriver bit or a smaller handle which carries a screwdriver bit.

35 DE 8404176.5 U1 has disclosed a screwdriver handle which is hollow. The cavity that is open towards the end side of the handle is covered by a cap which forms a cover. To actuate a pressure zone, it is possible to displace a latching
40 tongue of the cover in order to open the latter. Then, screwdriver blades disposed in the cavity can be removed.

DE 20015484 U1 has disclosed a handle for a screwdriver, in which the handle has two handle parts that can pivot open

about a pivot axis parallel to the handle axis. The handle parts form cavities into which tools and also screwdriver bits can be fitted. The two handle parts are latched closed by a closure tab.

5

US 4,934,223 describes a screwing tool resembling a piston grip, with a magazine which is disposed in the grip and can be pulled out through an end-side opening in the grip. Screwdriver bits fit into the magazine.

10

DE 29414974 U1 describes a handle of a screwdriver which comprises two parts fitted into one another. A handle part which includes a cavity has an opening into which a second handle part, which carries the blade, is fitted in its entirety. The handle part which carries the blade stores screwdriver bits.

15

Working on the basis of the prior art described in the introduction, the invention is based on the object of further developing the handle of the generic type in a manner advantageous for use. The object is achieved by the invention described in the claims.

20

SUMMARY OF THE INVENTION

25

~~Claim 1~~ The invention provides first and foremost that the latching means can be moved out of their latching position by pressure on an actuating zone associated with the end side of the handle. The handle is preferably elongate in form, with two end sides that face away from one another. The blade or a blade holder can project out of one end side. The other end side forms a handle cup which lies in the palm of the hand when the handle is gripped as it is taken hold of. In a first variant of the invention, this end side of a screwdriver handle, which is also referred to as the cup, is to form the actuating zone. It is preferable for the actuating zone to be formed by a push-button. This push-button is preferably located in a pot-shaped cutout in the end side of the handle. The end face of the push-button may in this case have a central hollow. The edge of this hollow may project beyond the opening edge of the cutout. The push-button preferably has soft or rounded edges, such that it

30

35

40

does not dig into the user's hand to a disruptive extent when the handle is gripped. In a preferred configuration of the invention, the latching of the two handle parts is only eliminated when the push-button has been displaced a certain
5 distance into the cutout. The latching is cancelled in particular when the end face of the push-button is located below the opening edge of the cutout. This configuration effectively avoids inadvertent cancelling of the latching. The latching means may be a spring tongue which has a
10 latching projection at its free end and which interacts with a latching step. The spring tongue may in this case be associated with the core part and the latching step with the handle part that includes the cavity. In this case, the spring tongues, which may be formed integrally with the
15 material of the core, project in the axial direction from the end portion of the core. It is possible to provide a plurality of spring tongues located diametrically opposite one another. It is preferable for these spring tongues to be displaced by actuating cams of the push-button. For this
20 purpose, the spring tongues may have control slopes which are acted on in a corresponding way by the actuating cam or a differently configured actuating element of the push-button. It is preferable for the two handle parts to be displaceable from the closed position into the open position
25 by the force of a prestressed spring after pressure on the actuating zone. The spring force is less than the latching force of the latching means. The spring stress can only be relieved after actuation of the push-button. In this case, in a preferred variant of the invention, the two handle
30 parts are moved apart until they reach a stop position, in which the screwdriver bits located in the storage chamber can be removed.

The object is also achieved by further embodiment of the
35 invention specified in Claim 12, which Claim 12 provides first and foremost that the latching means leaves its latching position through pressure on an actuating zone. The mating catch may be a latching step. The actuating zone may be associated with the handle part that includes the cavity.
40 According to the invention, the cancelling of the latching, which is a precondition for the two handle parts to be moved apart, can only be done deliberately by pressing on the

actuating zone. In a preferred refinement of the invention, it is provided that the latching means is a pivotable spring tongue which has a latching projection at its free end. This spring tongue is located with its latching projection in front of a step of the handle part that includes that cavity. Only when the spring tongue is displaced radially inward, so that the latching projection is moved out of the path of movement of the latching step, can the two handle parts be moved axially apart in order for the storage chamber to be opened. For the radial displacement of the latching projection, it is necessary to press on the actuating zone. This pressure continues through the wall of the cavity on to the spring tongue. It is preferable for the actuating zone to be formed by a soft plastic inlay in the outer wall of the handle part that includes the cavity. It is advantageous if two latching means, each with an associated actuating zone, are located diametrically opposite one another. The two actuating zones are then offset by 180° with respect to one another. When the screwdriver handle is gripped, there is no harm if pressure is applied to just one of the two actuating zones during the screwing action. It has been found that in the standard grip positions of the hand, a diametral pressure is not exerted with respect to the handle. When the handle is gripped, the thumb presses against the handle lateral surface on one side. The handle is held by the index finger on the diametrically opposite side. In this case, the zone of the handle lateral surface which lies diametrically opposite the thumb is in the joint crook between the second and third phalanxes of the index finger. Even if the handle is gripped from above, no two diametrically opposite zones are subject to the application of pressure. The axial portion in which the two diametrically opposite actuating zones are located is held between thumb, index finger and ring finger in a three-point grip. In a refinement of the invention, it is provided that the spring tongue is formed integrally with the material of the core. In this case, the spring tongue may be formed by a wall section of a wall of a compartment for receiving a screwdriver bit. Furthermore, it is advantageous if the application of radial force to the latching means does not take place directly via the soft plastic inlay, but rather via an actuating arm and an

actuating cam formed by it. The actuating cam in this case presses on the spring tongue in order to pivot it. The actuating arm may be formed by a U-shaped cut-free part of a hard plastic sleeve which forms the grip part that
5 includes the cavity.

Overall, however, the object is also achieved by yet another embodiment of the invention ~~specified in Claim 20~~ as described hereinafter.

10

The two handle parts may be spring-loaded with respect to one another in such a manner that, after the cancelling of the latching, they are displaced by a compression spring, which is stressed in the closed position, as a result of the
15 stresses in the compression spring being relieved, until they reach an open position. It is preferable for the two handle parts only to be displaced into a partially open position. The compression spring can be supported on the base of the cavity and on the end side of the core. The
20 compression spring can be secured at the base of the cavity by means of a centering projection. The other end of the compression spring can project into a guide recess in the end side of the core. In a refinement of the invention, it is provided that the two handle parts latch together in the
25 fully open position. The latching is in this case achieved with the aid of the actuating cam of the actuating arm. During the opening displacement, it is lifted over the latching cam. To displace the two handle parts from the fully open position back toward the closed position, the
30 actuating cam has to be lifted over the latching cam by the application of an axial force. In the fully open position, the actuating cam comes to a stop against a stop. This stop cannot be overcome in the axial separating direction of the two handle parts. However, plug-assembly of the two handle
35 parts is possible on account of rear-side slopes of the actuating cam, on the one hand, and of the stop, on the other hand, interacting with one another. It is preferable for the handle part which includes the core to be provided with a blade or with an exchangeable shank. The handle part
40 which includes the cavity is preferably provided, as a sleeve part, with a handle cup.

In principle, the object on which the invention is based is achieved by each of the claims individually.

BRIEF DESCRIPTION OF THE DRAWINGS

5

Exemplary embodiments are explained below with reference to the accompanying drawing, in which:

10 Fig. 1 ~~shows the handle of a screwing tool without a blade, as seen in the closed position,~~

Fig. 2 ~~shows an illustration corresponding to Figure 1 but in the open position,~~

15 Fig. 3 ~~shows an illustration corresponding to section III-III in Fig. 1,~~

Fig. 4 ~~shows excerpt IV in Fig. 3,~~

20 Fig. 5 ~~shows a section on line V-V in Fig. 2,~~

Fig. 6 ~~shows a section on line VI-VI in Fig. 3, and~~

25 Fig. 7 ~~shows a plan view of the handle part 2 with soft plastic inlays removed in the region of the actuating zone,~~

Fig. [[8]] 1 shows the end [[side]] view of ~~a second~~ an exemplary embodiment of the invention,

30 Fig. [[9]] 2 shows a section on line ~~IX-IX~~ II-II in Fig. [[8]] 1 in the latching position, in which the storage chamber is closed,

35 Fig. [[10]] 3 shows a section on line [[X-X]] III-III in Fig. [[8]] 1, likewise in the closed position,

Fig. [[10a]] 4 shows an enlarged excerpt from Fig. [[10]] 3 corresponding to line ~~Xa-Xa~~ IV-IV,

40

Fig. [[11]] 5 shows an illustration corresponding to Figure [[10]] 3 with the end-side push-button depressed,

Fig. [[12]] 6 shows an illustration corresponding to Fig. [[9]] 2 in the open position, [[and]]

5 Fig. [[13]] 7 shows an illustration corresponding to Fig. [[10]] 3 in the open position[[]].

Figs. 8-9 show perspective views of the handle with an axial portion being cut away to show interior components of the handle, and

Fig. 10 is an end view of the handle, partially sectioned to show interior components of the handle.

15

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

The handle illustrated in Figures 1 to 7 can be provided with a fixed blade or an exchangeable shank. The blade or
20 the exchangeable shank is accommodated in a blade receiving part 23. The way in which the exchangeable shank in question here functions is described in detail in DE 10233866.3, for which reason the disclosure content of this application is hereby incorporated in its entirety.

25

The handle substantially comprises two parts. Handle part 1 is a core part. Handle part 2 is a sleeve part. There is a cavity 3 in the sleeve part 2. ~~The cavity wall 13, on the outer wall side, has depressions 24 which are filled with soft plastic. The result, therefore, is two successive sequences of soft plastic material. The handle section of largest diameter is disposed between the two sequences. The lateral surface parting gap between the two handle parts 1, 2 is located in the region of a portion of locally enlarged diameter which directly adjoins the twisting zone. The middle, annular-concave portion of the handle lateral surface forms two opposite actuating zones 8 by means of one of its soft plastic inlays. Beneath each soft plastic inlay, the base of the depression 24 is provided with a U-shaped cut-free section 25. As a result of this cut-free section 25, an actuating arm 14 is formed. The free end of the~~

~~actuating arm 14 forms a radially inwardly projecting
actuating cam 15.~~

The handle part 1 has a core 4 which receives the blade or
5 the exchangeable shank. In the closed position illustrated
in Figure 3, this core is located entirely within the cavity
3. On the outer side, the core has a plurality of
compartments running in the axial direction. In each of
these compartments there is a screwdriver bit 11. In the
10 open position of the storage chamber 6 formed by these
compartments (cf. Fig. [[5]] 6), the screwdriver bits can be
removed or inserted again.

Two diametrically opposite walls 10, which separate the
15 individual compartments from one another, in each case
continue into spring tongues 5. These spring tongues 5 have
radially outwardly directed latching projections 9. In the
closed position illustrated in Figure 3 and Figure 4, the
two latching projections 9 are located in front of a
20 latching step 7 of the handle part 2. This prevents axial
displacement of the two handle parts 1, 2 with respect to
one another. The latching projections 9 can only be moved
out of the movement path of the latching steps 7 by pivoting
of the actuating arms 14 as a result of pressure being
25 directed radially inward on both the diametrically opposite
soft zones 8 simultaneously, so that it is possible for the
two handle parts 1, 2 to be displaced with respect to one
another. This is done by the actuating cam 15 forcing the
spring tongue 5 radially inward, so that it pivots
30 elastically.

The end side of the core 4 has a cylindrical extension which
forms a guide recess 17. In the closed position, a
compressed compression spring 16 is located in this guide
35 recess 17. The end edge of the guide recess 17 in this case
butts against the cavity base 3' of the cavity 3. A
centering projection 20 for the compression spring 16
projects into the opening of the guide recess 17.

40 If the latching between the two handle parts 1, 2 is
cancelled as described above by simultaneous pressure on the
two opposite soft zones 8, the stress of the spring 16 can

be relieved. The relieving of the stress in the compression spring 16 leads to partial opening of the storage chamber 6 until it reaches the position illustrated in Figure [[2]] 6. In this position, the stress in the compression spring 16
5 has been completely relieved.

~~By applying an axial pull to the two handle parts 1, 2, it is possible to reach the fully open position illustrated in Figure [[5]] 6. In the end phase of the displacement in the~~
10 ~~direction of this fully open position, the actuating cam 15 of the actuating arm 14 moves over a latching cam 18 of the core 4. In the fully open position, a rear flank of the actuating cam 15 comes to a stop against a stop 19. The front flank of the actuating cam 15 is inclined. The rear~~
15 ~~flank of the stop 19 is likewise inclined. During plug-fitting association of the two handle parts for the purpose of assembling the handle, these two slopes interact as run-on slopes.~~

20 ~~To close the storage chamber 6 again, the handle part 2 that includes the cavity 3 has to be displaced in the axial direction toward the handle part 1. The latching engagement which is formed by the interaction of the latching cam 18 with the actuating cam 15 is in this case overcome by an~~
25 ~~axial pressure.~~

The closed position illustrated in Figure [[4]] 3 is reached as a result of a slope of the latching projection 9 interacting with a slope of the latching step 7. In the
30 final phase of the closing movement, the two slopes slide along one another. This is associated with elastic pivoting of the spring tongue 5 in the radially inward direction.

In the case of the handle illustrated in Figures [[8]] 1 to
35 [[13]] 10, the latching is cancelled by pressure on a push-button 8 which is associated with the end side of the handle part 2. The handle part 2 has an inner cavity 3. The core 4 of a second handle part 1 fits into this cavity 3. The core 4 has circumferentially disposed receiving chambers 6 for
40 screwdriver bits 11. The individual storage chambers 6 are separated from one another by means of walls. Furthermore, the core 4 has a cavity for the insertion of a blade. The

core 4 also has a rear axial extension 31, from which a total of four diametrically opposite spring tongues 5 originate. Each spring tongue forms a latching projection 9 (Figs 8-9) with a control slope 30. The axial extension 31 fits inside a compression coil spring 16, the end of which is supported on a shoulder 34 of the core 4. The other end of the compression coil spring 16 is supported on the base of the cavity 3. The core 4 is spring-loaded in the direction of the opening of the cavity 3 in the handle part 2 by means of the compression spring 16.

The core has a radially protruding stop 32 in the form of a projection. In the same axial position with respect to the stop 32, the cavity 3 also has a stop 33, against which the stop 32 strikes when the spring 16 has pressed the two handle parts 1, 2 apart. The stop 33 projects radially inward from the wall of the cavity 3. The core 4 is mounted axially displaceably but non-rotatably in the cavity 3. As a result, torques can be transmitted from the handle part 2 to the handle part 1.

That end of the handle part 2 which forms the cup of the handle part 2 has a pot-shaped cutout 26 (Fig.9). The base of the pot-shaped cutout 26 has a central aperture, through which holding arms 35 (Figs. 2, 10) of a push-button, which is spring-loaded in the opening direction of the cutout 26 by means of a compression spring 27, protrude. Hook-like end portions of the holding arms are responsible for axially holding the push-button 8 in the cutout 26 associated with it.

Axially offset with respect to the holding arms 35, actuating cams of the push-button 8 protrude into the cutout 26. In the closed position, these actuating cams 29 are located in front of the end-side control slopes 30 of the spring tongues 5. In the closed position, the end portions, forming the latching projection 9, of the spring tongues project through the base opening of the cutout 26 into the cutout 26, in such a manner that the latching projections 9 engage over the edge of the base opening. These zones over which the latching projections 9 have engaged form a latching step 7.

In the closed position (Figures ~~9, 10~~ 2, 3), the compression spring 16 is stressed. If the push-button is pressed in this state, as shown in Figure 11, the control slopes 30 of the spring tongues 15 are acted on by the actuating cams 29.

5 Pressing the push-button 8 causes the end edge of the actuating cam to slide along the control slope 30. In association with this sliding movement, the end portion of the spring tongue 5 is displaced radially inward. As long as the end face of the push-button 8 is above the opening edge

10 28 of the cutout, the latching projections 9 engage behind the latching steps 7 associated with them. Only when the end face of the push-button 8 is entirely within the cutout 26 are the spring tongues 5 bent radially inward to such an extent that the latching projections 9 are moved out of

15 latching engagement with respect to the latching steps. Then, the stress in the compression spring 16 is relieved, and the compression spring displaces the handle part 1 which includes the core 4 into the open position illustrated in Figures ~~[[12]] 6 and [[13]] 7~~, in which the stops 32, 33 are

20 in contact with one another. In this open position, the compression spring 16 still has a small residual stress.

If, starting from the open position illustrated in Figures ~~[[12]] 6 and [[13]] 7~~, the core 4 is pushed back

25 into the cavity, the compression spring 16 is stressed. The control slopes 30 act on inclined control surfaces of the latching step 7. In the final phase of the insertion movement of the core 4 into the cavity 3, the latching projections 9 engage behind the latching steps 7 associated

30 with them. In the process, the control slopes 30 slide along the latching step 7 until they engage behind the latching step 7 with a snap action.

~~All features disclosed are (inherently) pertinent to the~~

35 ~~invention. The disclosure content of the associated/appende~~
~~priority documents (copy of the prior application) is hereby~~
~~incorporated in its entirety in the disclosure of the~~
~~application, partly with a view to incorporating features of~~
~~these documents in claims of the present application.~~